

# High performance. Low price. You game?

HyperX® FURY solid-state drive delivers impressive performance at an affordable price, to get you into the game faster and improve your gameplay. Ideal for desktops and notebooks, it features a slim 7mm form factor and SandForce® SF-2281 controller with SATA Rev 3.0 (6Gb/s) performance. The result is faster system boot up, application loading and file execution plus faster map and level load time. Its synchronous NAND allows for higher and consistent drive performance. So you're not only in the game, you're winning it.

In 120GB and 240GB capacities, HyperX FURY SSD is available as a stand-alone drive and is easy to install. This cost-efficient upgrade is less disruptive than buying a new system to increase performance. The new FURY entry-level product line from HyperX includes memory and SSDs and is designed for gamers, enthusiasts and system Integrators, who can now have consistent HyperX branding for their gaming PCs.

Built with Flash memory, HyperX FURY SSD has no moving parts and is cooler, quieter and more shock- and vibration-resistant than traditional hard drives, making it the ideal hard drive replacement. It's backed by a three-year warranty and free technical support.

- > SandForce controller with SATA Rev 3.0 (6Gb/s) performance
- > Read/write speeds of 500/500 MB/s
- > Features synchronous NAND for consistent high SSD performance




### HyperX FURY SSD is ideal for:

- Faster system boot up times, application loading & file execution
- Faster map and level load times in game with increased frames per second

#### Features/specs on reverse $\rangle\rangle$





# **HyperX FURY SSD**

### FEATURES/BENEFITS

- > Fast boosts overall system responsiveness and performance
- > Improved gameplay dramatically reduces game and level loading times to get into the game faster
- > Slim 2.5-inch drive available in 7mm to fit in more systems (even slimmer notebooks)
- > Reliable cool, rugged and durable drive to push your system to the limits
- > Cost-effective offers the perfect combination of price/performance for budget-minded users

### SPECIFICATIONS

- > Form factor 2.5"
- > Interface SATA Rev. 3.0 (6Gb/s) with backwards compatibility to SATA Rev. 2.0
- > Capacities<sup>1</sup> 120GB, 240GB

> **Baseline performance**<sup>2</sup> Compressible data transfer (ATTO) All capacities: 500MB/s read and 500MB/s write Incompressible data transfer (AS-SSD and CrystalDiskMark) 120GB — 420MB/s read and 120MB/s write 240GB — 470MB/s read and 220MB/s write Maximum 4k Read/Write 120GB — up to 84,500/ up to 52,000 IOPS 240GB — up to 84,500/ up to 41,000 IOPS Random 4k Read/Write 120GB — up to 11,500/ up to 52,000 IOPS 240GB — up to 22,500/ up to 41,000 IOPS PCMark® Vantage HDD Suite Score 120GB — 60,000 240GB — 60.000 PCMark 8 storage bandwidth 120GB - 140 MB/s 240GB - 180 MB/s > Total Bytes Written (TBW)<sup>3</sup> 120GB: 354TB 2.75 DWPD<sup>4</sup> 240GB: 641TB 2.5 DWPD4 > Power consumption 0.31 W idle / 0.35 W avg / 1.65 W (MAX) read / 2.76 W (MAX) write > Storage temperature -40°C~85°C > Operating temperature 0°C~70°C

- > Dimensions 69.8mm x 100.1mm x 7mm
- > Weight 90.03g
- > Vibration operating 2.17G peak (7–800Hz)
- > Vibration non-operating 20G peak (10-2000Hz)
- > Life expectancy 1 million hours MTBF
- > Warranty/support three-year warranty with free technical support

This SSD is designed for use in desktop and notebook computer workloads and is not intended for server environments. This Job's designed to lose in observed and the second complete workback and a not interface to serve eminimisers. Some of the listed capacity on a Flash storage device is used for formulating and other functions and is thus not available for data storage. As such, the actual available capacity for dat storage is less than what is listed on the products. For more information, go to Kingstor's Flash memory Guide at kingstora.com/flashguide.

2 Based on "out-of-box performance" using a SATA Rev. 3.0 motherboard. Speed may vary due to host hardware, software and usage. IOMETER random 4k random read/write is based on 8GB partition. 3 Total Bytes Written (TBW) is derived from the JEDEC Client Workload (JESD219A). 4 Drives Writes Per Day (DWPD)

HyperX is a division of Kingston

THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2014 Kingston Technology Europe Co LLP and Kingston Digital Europe Co LLP, Kingston Court, Brooklands Close, Sunbury-on-Thames, Middlesex, TW16 7EP, England. Tel: +44 (0) 1932 738888 Fax: +44 (0) 1932 785469. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-287EN



## HYPERX PART NUMBERS

SHFS37A/120G SHFS37A/240G



